



# LAKE SIDE FLOOD SOLUTIONS

## LFS 333 SUBMERSIBLE FLOOD PUMP



## PRODUCT DATA SHEET





**LAKESIDE**  
FLOOD SOLUTIONS

## LFS 333 Submersible Flood Pump

Robust housing designed to pump dirty water.  
Passes up to 35mm solids/debris.  
Pumps down to 35mm.

### Key features:

- Pumps water down to 35mm
- Float switch control allows for automatic operation
- Stainless Steel; non-corrosive and durable
- Removes dirty water with particles up to 35mm
- Ceramic sealing improves waterproof function
- Temperature protection, motor automatically switches off if over-heating

## PRODUCT DATA SHEET

### Specification:

- Output: 20,000 litres per hour;  
333 litres per minute
- Power: 1100W 230V~50 Hz
- Solids: up to 35mm
- Maximum delivery height: 9m
- Maximum operating depth: 7m
- Stainless Steel Housing
- Certification: CE certification, IPX8 (Water Immersion Test)
- Length of cable: 10m
- Outlet: Universal fitting 1" or 1 1/4" or 1 1/2"

### Materials:

- Pump body: Stainless Steel
- Handle, Base: PP-GF20
- Shaft: Carbon Steel
- Winding: Aluminum
- Motor Housing: Steel
- Sealing: Ceramic



01792 561117

[sales@lakesidefloodsolutions.co.uk](mailto:sales@lakesidefloodsolutions.co.uk)

Bruce Road, Fforestfach Industrial Estate, Swansea SA5 4HS



[www.lakesidefloodsolutions.co.uk](http://www.lakesidefloodsolutions.co.uk)